



<https://www.verfschilderen.nl/boero-thinner-pro.html>

YachtCoatings

# THINNER PRO

## TECHNICAL DATA SHEET

### Product description

Specific thinner for temperatures that may vary from 18° to 25°. Suitable for spray applications of products of the Challenger PRO line.

### Product information

Finish	Liquid		
Colour	Colourless. 000		
Specific gravity	UNI EN ISO 2811-1		0,90 ÷ 0,95 g/cm <sup>3</sup>
Flash Point	UNI EN ISO 13736		18 °C
VOC (calculated average content)	ISO 11890-2/2006		574 g/l
Packaging	1 – 5 Lt		

### Storage

It is recommended to avoid exposure to air and extreme temperatures. To maximize the shelf life in the can, it is worth checking that the container is well closed during the storage and the temperature is between 10 °C and 35 °C. Avoid exposure to direct sunlight.



*YachtCoatings*

# THINNER PRO

## TECHNICAL DATA SHEET

### Safety rules

---

Observe the provisions of DPR 303 and 547. Avoid contact with the skin, for example. Operate in well ventilated places and, if in closed areas, use vacuum cleaners, fans and air conveyors. During the application use appropriate protections (masks, gloves, glasses, etc.). Before using, read sections 7-8 of the SDS.

#### INSTRUCTIONS FOR THE DISPOSAL OF PRODUCTS AND PACKAGING

Empty packaging that contained products: Dispose of empty packaging according to the requirements of the waste disposal law, for example by taking them to the recycling center.

Packages containing the unused products: Dispose of the unused product in accordance with the law of disposal of such waste, for example by taking it to a recycling center, recycling of packaging is prohibited in this case. Do not empty into drains or watercourses. Product packaging must be kept indoor, and the temperature in the storage place must be between 10 °C and 35 °C. Do not expose to sunlight.

### Notes

---

The values indicated in the present technical sheet can have slight variations from one batch to another. All data refer to the mixed product. The applied product must not come in contact with water, chemicals or subjected to mechanical stress before the curing is complete. The above information is the result of accurate laboratory tests and practical experience; however, since the product is predominantly used outside the manufacturer's control, Boero Bartolomeo S.p.A. can only guarantee its quality. The information contained in this sheet may be subject to revision by the Company. For clarification, updates or further information, it is recommended to contact Boero Bartolomeo S.p.A. directly. The present datasheet annuls and replaces every other precedent to this one.