

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 05.05.2015

Version number 1

Revision: 05.05.2015

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**- 1.1 Product identifier**

**- Trade name:** **COELAN Boat Flexo Primer**

**- 1.2 Relevant identified uses of the substance or mixture and uses advised against** <https://www.verfschilderen.nl/coelan-flexo-hechtprimer-250ml.html>  
 No further relevant information available.

**- Application of the substance / the mixture** Priming

**- 1.3 Details of the supplier of the safety data sheet**

**- Manufacturer/Supplier:** KEMPER SYSTEM GmbH & Co. KG  
 Holländische Strasse 32-36  
 34246 Vellmar  
 Deutschland / Germany  
 Telefon: +49 (0)561 / 8295-0  
 Telefax: +49 (0)561 / 8295-5110  
 E-Mail: MSDS@KEMPER-SYSTEM.COM

**- Further information obtainable from:**

**- 1.4 Emergency telephone number:** Research and Development  
 Giftinformationszentrum der Länder Rheinland-Pfalz und Hessen  
 Langenbeckstraße 1; Gebäude 601; 55131 Mainz  
 Tel. Nr.: +49 (0)6131 / 19 24 0  
 Universitätsmedizin der Johannes Gutenberg-Universität Mainz

**SECTION 2: Hazards identification**

**- 2.1 Classification of the substance or mixture**

**- Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3      H226      Flammable liquid and vapour.



GHS08 health hazard

Resp. Sens. 1      H334      May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 Carc. 2            H351      Suspected of causing cancer.  
 STOT RE 2        H373      May cause damage to organs through prolonged or repeated exposure.  
 Asp. Tox. 1        H304      May be fatal if swallowed and enters airways.



GHS09 environment


Aquatic Chronic 2 H411      Toxic to aquatic life with long lasting effects.




GHS07

Skin Irrit. 2        H315      Causes skin irritation.  
 Eye Irrit. 2        H319      Causes serious eye irritation.  
 Skin Sens. 1        H317      May cause an allergic skin reaction.  
 STOT SE 3        H335-H336      May cause respiratory irritation. May cause drowsiness or dizziness.


**- Classification according to Directive 67/548/EEC or Directive 1999/45/EC**




R40-48/20-65:      Limited evidence of a carcinogenic effect. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Harmful: may cause lung damage if swallowed.



R42/43:            May cause sensitisation by inhalation and skin contact.



R36/37/38:        Irritating to eyes, respiratory system and skin.



R51/53:            Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
 R10-67:            Flammable. Vapours may cause drowsiness and dizziness.

(Contd. on page 2)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.05.2015

Version number 1

Revision: 05.05.2015

Trade name: **COELAN Boat Flexo Primer**

(Contd. of page 1)

**- Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

**- Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

**- 2.2 Label elements**

**- Labelling according to Regulation (EC) No 1272/2008**

**- Hazard pictograms**

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07 GHS08 GHS09

**- Signal word**

Danger

**- Hazard-determining components of labelling:**

hydrocarbons, C9, aromatic

Isocyanic acid, polymethylenepolyphenylene ester

Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate 4,4'-methylenediphenyl diisocyanate

**- Hazard statements**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

**- Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**- Additional information:**

EUH204 Contains isocyanates. May produce an allergic reaction.

**- 2.3 Other hazards**

**- Results of PBT and vPvB assessment**

**- PBT:**

Not applicable.

**- vPvB:**

Not applicable.

## SECTION 3: Composition/information on ingredients

**- 3.2 Chemical characterisation: Mixtures**

**- Description:**

Mixture of substances listed below with nonhazardous additions.

**- Dangerous components:**

EC number: 918-668-5	hydrocarbons, C9, aromatic Xn R65; Xi R37; N R51/53 R10-66-67 Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	50-100%
CAS: 9016-87-9 EC number: 618-498-9	Isocyanic acid, polymethylenepolyphenylene ester Xn R20-40-48/20/21/22; Xn R42/43; Xi R36/37/38 Carc. Cat. 3 Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	12.5-25%
EC number: 905-806-4	Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate Xn R20-40-48/20; Xi R36/37/38 Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	0.5-2.5%

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 05.05.2015

Version number 1

Revision: 05.05.2015

**Trade name: COELAN Boat Flexo Primer**

		(Contd. of page 2)
CAS: 101-68-8 EINECS: 247-714-0	4,4'-methylenediphenyl diisocyanate Xn R20-40-48/20; Xn R42/43; Xi R36/37/38 Carc. Cat. 3 Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	0.5-2.5%
CAS: 77-58-7 EINECS: 201-039-8	dibutyltin dilaurate T Repr. Cat. 2 R60-61-48/25; C R34; Xn R68; Xi R43; N R50/53 Muta. Cat. 3 Muta. 2, H341; Repr. 1B, H360FD; STOT SE 1, H370; STOT RE 1, H372; Skin Corr. 1C, H314; Aquatic Chronic 1, H410; Skin Sens. 1, H317	< 0.5%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.  
Rinse opened eye for several minutes under running water.  
If symptoms persist consult doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.  
Alcohol resistant foam  
ABC powder
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.  
Keep away from ignition sources.
- **6.2 Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.  
Prevent from spreading (e.g. by damming-in or oil barriers).
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections** See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Store in cool, dry place in tightly closed receptacles.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.  
Use only in well ventilated areas.  
Extractor required at the object.
- **Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.

(Contd. on page 4)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.05.2015

Version number 1

Revision: 05.05.2015

Trade name: **COELAN Boat Flexo Primer**

(Contd. of page 3)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Protect from frost.  
Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

### - Ingredients with limit values that require monitoring at the workplace:

#### 101-68-8 4,4'-methylenediphenyl diisocyanate

WEL	Short-term value: 0.07 mg/m <sup>3</sup> Long-term value: 0.02 mg/m <sup>3</sup> Sen; as -NCO
-----	---

#### 77-58-7 dibutyltin dilaurate

WEL	Short-term value: 0.2 mg/m <sup>3</sup> Long-term value: 0.1 mg/m <sup>3</sup> as Sn; Sk
-----	--

### - DNELs

#### Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate

Dermal	Acute - local effects	28.7 mg/cm <sup>2</sup> (worker)
	Acute - systemic effects	50 mg/kg (worker)
Inhalative	Acute - local effects	0.1 mg/m <sup>3</sup> (worker)
	Acute - systemic effects	0.1 mg/m <sup>3</sup> (worker)
	Long term - local effects	0.05 mg/m <sup>3</sup> (worker)
	Long term - systemic effects	0.05 mg/m <sup>3</sup> (worker) 0.025 mg/m <sup>3</sup> (consumer)

#### 101-68-8 4,4'-methylenediphenyl diisocyanate

Dermal	Acute - systemic effects	50 mg/kg (worker)
Inhalative	Acute - local effects	0.1 mg/m <sup>3</sup> (worker)
	Acute - systemic effects	0.1 mg/m <sup>3</sup> (worker)
	Long term - local effects	0.01 mg/m <sup>3</sup> (worker)
	Long term - systemic effects	0.05 mg/m <sup>3</sup> (worker)

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:** Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- **Respiratory protection:** In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.  
Use suitable respiratory protective device in case of insufficient ventilation.
- **Protection of hands:**



Protective gloves

Only use chemical-protective gloves with CE-labelling of category III.  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves** The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

(Contd. on page 5)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.05.2015

Version number 1

Revision: 05.05.2015

Trade name: **COELAN Boat Flexo Primer**

(Contd. of page 4)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material:  $\geq 0.7$  mm

Synthetic rubber gloves

**- Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Value for the permeation: Level  $\leq 3$

**- Eye protection:**



Tightly sealed goggles

**- Body protection:**

Protective work clothing

Impervious protective clothing

## SECTION 9: Physical and chemical properties

**- 9.1 Information on basic physical and chemical properties**

**- General Information**

**- Appearance:**

Form: Fluid

Colour: According to product specification

- Odour: Characteristic

- Odour threshold: Not determined.

- pH-value: Not determined.

**- Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Undetermined.

- Flash point:  $> 35$  °C

- Flammability (solid, gaseous): Not applicable.

**- Ignition temperature:**

Decomposition temperature: Not determined.

- Self-igniting: Product is not selfigniting.

- Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

**- Explosion limits:**

Lower: Not determined.

Upper: Not determined.

- Density at 20 °C: 0.94 g/cm<sup>3</sup>

- Relative density: Not determined.

- Vapour density: Not determined.

- Evaporation rate: Not determined.

**- Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

- Partition coefficient (n-octanol/water): Not determined.

**- Viscosity:**

Dynamic: Not determined.

Kinematic at 23 °C: 11 s (DIN EN ISO 2431)

**- Solvent content:**

VOC (EC) 79.80 %

- 9.2 Other information: No further relevant information available.

## SECTION 10: Stability and reactivity

**- 10.1 Reactivity**

**- 10.2 Chemical stability**

**- Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

**- 10.3 Possibility of hazardous reactions**

No dangerous reactions known.

**- 10.4 Conditions to avoid**

No further relevant information available.

(Contd. on page 6)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.05.2015

Version number 1

Revision: 05.05.2015

Trade name: **COELAN Boat Flexo Primer**

(Contd. of page 5)

- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

## SECTION 11: Toxicological information

### - 11.1 Information on toxicological effects

#### - Acute toxicity

#### - LD/LC50 values relevant for classification:

##### hydrocarbons, C9, aromatic

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

##### 9016-87-9 Isocyanic acid, polymethylenepolyphenylene ester

Oral	LD50	>10000 mg/kg (rat)
Dermal	LD50	>9400 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)

##### Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate

Oral	LD50	>10000, mg/kg (rat)
Dermal	LD50	>9400 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (ATE)

##### 101-68-8 4,4'-methylenediphenyl diisocyanate

Oral	LD50	2200 mg/kg (mouse)
		>10000 mg/kg (rat)
Dermal	LD50	>9400 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (ATE)

##### 77-58-7 dibutyltin dilaurate

Oral	LD50	2071 mg/kg (rat) (OECD 401)
------	------	-----------------------------

#### - Primary irritant effect:

#### - Skin corrosion/irritation

Irritant to skin and mucous membranes.

#### - Serious eye damage/irritation

Irritating effect.

#### - Respiratory or skin sensitisation

Sensitisation possible through inhalation.

Sensitisation possible through skin contact.

#### - Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

#### - CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carc. 2

## SECTION 12: Ecological information

### - 12.1 Toxicity

#### - Aquatic toxicity:

##### 77-58-7 dibutyltin dilaurate

EC50	3.1 mg/l (Brachydanio rerio (Ricefish))
	1 mg/l (Scenedesmus subspicatus)
	0.463 mg/l (Daphnia magna)

#### - 12.2 Persistence and degradability

No further relevant information available.

#### - 12.3 Bioaccumulative potential

No further relevant information available.

#### - 12.4 Mobility in soil

No further relevant information available.

#### - Ecotoxicological effects:

#### - Remark:

Toxic for fish

#### - Additional ecological information:

#### - General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms

#### - 12.5 Results of PBT and vPvB assessment

#### - PBT:

Not applicable.

#### - vPvB:

Not applicable.

#### - 12.6 Other adverse effects

No further relevant information available.

GB

(Contd. on page 7)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.05.2015

Version number 1

Revision: 05.05.2015

Trade name: **COELAN Boat Flexo Primer**

(Contd. of page 6)

## SECTION 13: Disposal considerations



- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **European waste catalogue**

08 04 09*	waste adhesives and sealants containing organic solvents or other dangerous substances
08 04 10	waste adhesives and sealants other than those mentioned in 08 04 09

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

## SECTION 14: Transport information



- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1263
- **14.2 UN proper shipping name**
- **ADR** 1263 PAINT, ENVIRONMENTALLY HAZARDOUS
- **IMDG** PAINT (hydrocarbons, C9, aromatic, dibutyltin dilaurate), MARINE POLLUTANT
- **IATA** PAINT
- **14.3 Transport hazard class(es)**
- **ADR**

	
---	--

- **Class** 3 (F1) Flammable liquids.
- **Label** 3

---


- **IMDG**

	
--	---

- **Class** 3 Flammable liquids.
- **Label** 3

---

- **IATA**


--

- **Class** 3 Flammable liquids.
- **Label** 3
- **14.4 Packing group**
- **ADR, IMDG, IATA** III
- **14.5 Environmental hazards:** Product contains environmentally hazardous substances: dibutyltin dilaurate, hydrocarbons, C9, aromatic
- **Marine pollutant:** Yes  
Symbol (fish and tree)
- **Special marking (ADR):** Symbol (fish and tree)
- **14.6 Special precautions for user** Warning: Flammable liquids.
- **Danger code (Kemler):** 30
- **EMS Number:** F-E,S-E
- **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **Transport/Additional information:**
- **ADR**
- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml
- **Transport category** 3

(Contd. on page 8)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.05.2015

Version number 1

Revision: 05.05.2015

Trade name: **COELAN Boat Flexo Primer**

(Contd. of page 7)

- Tunnel restriction code	D/E
- IMDG	
- Limited quantities (LQ)	5L
- Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
- UN "Model Regulation":	UN1263, PAINT, ENVIRONMENTALLY HAZARDOUS, 3, III

## SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture: No further relevant information available.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases	<p>H226 Flammable liquid and vapour.  H304 May be fatal if swallowed and enters airways.  H314 Causes severe skin burns and eye damage.  H315 Causes skin irritation.  H317 May cause an allergic skin reaction.  H319 Causes serious eye irritation.  H332 Harmful if inhaled.  H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  H335 May cause respiratory irritation.  H336 May cause drowsiness or dizziness.  H341 Suspected of causing genetic defects.  H351 Suspected of causing cancer.  H360FD May damage fertility. May damage the unborn child.  H370 Causes damage to organs.  H372 Causes damage to organs through prolonged or repeated exposure.  H373 May cause damage to organs through prolonged or repeated exposure.  H410 Very toxic to aquatic life with long lasting effects.  H411 Toxic to aquatic life with long lasting effects.</p> <p>R10 Flammable.  R20 Harmful by inhalation.  R34 Causes burns.  R36/37/38 Irritating to eyes, respiratory system and skin.  R37 Irritating to respiratory system.  R40 Limited evidence of a carcinogenic effect.  R42/43 May cause sensitisation by inhalation and skin contact.  R43 May cause sensitisation by skin contact.  R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.  R48/20/21/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.  R48/25 Toxic: danger of serious damage to health by prolonged exposure if swallowed.  R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p> <p>R60 May impair fertility.  R61 May cause harm to the unborn child.  R65 Harmful: may cause lung damage if swallowed.  R66 Repeated exposure may cause skin dryness or cracking.  R67 Vapours may cause drowsiness and dizziness.  R68 Possible risk of irreversible effects.</p>
--------------------	--

- Department issuing MSDS: research & development
- Contact: research & development
- Abbreviations and acronyms:
  - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
  - IMDG: International Maritime Code for Dangerous Goods
  - IATA: International Air Transport Association
  - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
  - EINECS: European Inventory of Existing Commercial Chemical Substances
  - ELINCS: European List of Notified Chemical Substances
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)
  - VOC: Volatile Organic Compounds (USA, EU)
  - DNEL: Derived No-Effect Level (REACH)
  - LC50: Lethal concentration, 50 percent

(Contd. on page 9)



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.05.2015

Version number 1

Revision: 05.05.2015

**Trade name: COELAN Boat Flexo Primer**

(Contd. of page 8)

LD50: Lethal dose, 50 percent  
Flam. Liq. 3: Flammable liquids, Hazard Category 3  
Acute Tox. 4: Acute toxicity, Hazard Category 4  
Skin Corr. 1C: Skin corrosion/irritation, Hazard Category 1C  
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2  
Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1  
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1  
Muta. 2: Germ cell mutagenicity, Hazard Category 2  
Carc. 2: Carcinogenicity, Hazard Category 2  
Repr. 1B: Reproductive toxicity, Hazard Category 1B  
STOT SE 1: Specific target organ toxicity - Single exposure, Hazard Category 1  
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3  
STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1  
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2  
Asp. Tox. 1: Aspiration hazard, Hazard Category 1  
Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

- \* Data compared to the previous version altered.

GB