



# TECHNICAL DATA SHEET

## 697. THINNER


Slow thinner for two component polyurethane's.

Packaging	0,13 – 0,66 U.S. gallons (0,5 - 2.5 Lt)
-----------	---


### TYPICAL CHEMICAL-PHYSICAL CHARACTERISTICS

Aspect	Transparent
Colour	Colourless
Specific gravity	53,55 ÷ 56,07 pound/feet <sup>3</sup> (0,85 ÷ 0,89 g/cm <sup>3</sup> )
Flash point	113 F (45 °C)
Physical state	Liquid


### CHARACTERISTIC DATA

Dilution rate		10 – 40%
Dilutes the following topcoats	Futura – Challenger HS – Challenger HT	

### SAFETY RULES

	In order to protect personal health it is advisable to comply with the EU DPR 303 and 547 regulations. Avoid, for example any contact of the product with the skin and eyes. In case of contamination or with oral contact, immediately contact a doctor. Use in well ventilated areas, in enclosed areas use aspirators, fans and air ventilators. Wear masks, goggles, gloves while applying the product.
---	---

### NOTES

	The applied product must not come in contact with water, chemical products or submitted to mechanical stress before the curing is completed. The wet film thickness is referring to an undiluted product. In case of dilution, this value increases. The above information is given to the best knowledge of Boero Bartolomeo Spa, based on laboratory tests and practical experience. However, as the product is often used under conditions beyond our control. Only the quality of the product can be guaranteed. Boero Bartolomeo Spa reserves the right to change the given data without notice. Further notes can be found in the "General recommendations" in the Supernavi paint website. For explanations, updates or further information we advise you to directly contact Boero Bartolomeo Spa The present datasheet annuls and replaces every other precedent to this one.
---	--