

Codice: 8E0000

## Thinner 203



THINNER FOR SYNTHETIC, ALKYD, GLYCEROPHTALIC, POLYACRYLIC AND POLYURETHANE TWO-COMPONENT PAINTS.

Our thinners are specifically formulated and balanced for use with our paints. All our products must be diluted necessarily and exclusively with our thinners recommended on the directions of use on each can or specified in the relevant product data sheets. The use of other thinners not specified in our technical information may affect the final result of our products. Our thinners are exclusively obtained with high quality solvent blends.

<https://www.verfschilderen.nl/aemme-thinner-203-05-liter.html>

### Technical Characteristics

<b>Paint Type</b>	Two components
<b>Specific gravity kg/lit (±0,05)</b>	0.900

#### SAFETY PRECAUTIONS

Before starting paint application please carefully read all the safety precautions indicated on the label of each can or in the product safety data sheet available on request. For further information please do not hesitate to contact our technical staff.

#### NOTES

The above information is given to the best of our current knowledge, however, because the conditions of use of our products are beyond our control, no warranty is given or to be implied in respect of such information. Our technical staff can be contacted to study customer's specific requirements involving our products in order to enable their most effective use. Dilution rates and drying times must be considered only indicative, mainly related to a temperature of 20 °C (68°F) and may vary according to prevailing temperature, in presence of particular weather conditions or depending on application procedures.